



BISAFE
MÄRKNING & INDUSTRI SÄKERHET



Sharp Edges Corner Protection

Data Sheet v2.1



CableSafe® / Westmark B.V.
Arnhemseweg 87, 3832 GK Leusden



046 - 70 51 20



info@bisafe.se

Confined Space Safety

Sharp Edges Corner Protection

Description

Contact with sharp edges is routine in many engineering jobs. Injuries are common:

1. Where people are involved in handling sheet or strip metal.
2. During work at presses, where small pieces of metal with sharp edges are handled frequently.
3. Following accidental contact with scrap metal, banding or swarf, principally during cleaning and disposal.
4. By contact with machinery blades, cutters or tools (for example when fitting, removing, cleaning or storing).

MODEL	CHARACTERISTICS
Sharp Edges Corner Protect Orange Magnet 65 kg	<ul style="list-style-type: none"> • Color: Orange • Dimensions: 150 x 150 mm • Weight: 254 gr • Traction magnet: 65 kg • Easy to mount on wooden constructions by means of screw or nail
Sharp Edges Corner Protect White 3M Cat. 3 Magnet 65 kg	<ul style="list-style-type: none"> • Color: White with 3M reflective film • Dimensions: 150 x 150 mm • Weight: 254 gr • Traction magnet: 65 kg

* Minimum order quantity of 20 pieces

Benefits

- > High safety level
- > Clear marking
- > Sustainable materials, Reusable
- > Applicable to steel (magnet), wood (Screws)
- > Stackable so space saving
- > Temporary or permanent protection and clear marking

Confined Space Safety

Sharp Edges Corner Protection

Images





OUR WORK AREA



CableSafe® / Westmark
B.V Arnhemseweg 87
3832 GK Leusden

